




TORTO™

FP7900** -220 Ceiling Fan



	A	B
Fan w/6" downrod	16.50"	12.00"
Fan w/12" downrod	22.50"	18.00"
Fan w/18" downrod	28.50"	24.00"
Fan w/24" downrod	34.50"	30.00"
Fan w/36" downrod	46.50"	42.00"
Fan w/48" downrod	58.50"	54.00"
Fan w/60" downrod	70.50"	66.00"
Fan w/72" downrod	82.50"	78.00"

INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 50 lbs.

ELECTRICAL REQUIREMENTS:

Requires a grounded electrical supply line of 220~240 volts AC, 50 Hz, 5 amp circuit.

MOTOR SPECS:

172 x 20-220 motor is designed for optimal performance with this fan.

BLADE SET:

A set of three composite blades is included.

CONTROL OPTIONS:

TR4WH-220 hand-held remote control is included. Push button remote control has 3 fan speeds, infinite light levels, reverse and off button. Optional C2-220 and C6-220 wall controls are available —sold separately. Instructions are provided with each control.

LIGHTING OPTIONS:

2-bulbs (bulb not included) built-in downlight fixture is included. Maximum downlight wattage is not to exceed 120 watts.

DOWNROD OPTIONS:

Fan comes with a 1" dia. x 6" long downrod (DR1-6). Optional downrods available in 12", 18", 24", 36", 48", 60" and 72" lengths. Fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 6" downrod. Optional close-to-ceiling kit is available as well—sold separately. Optional sloped ceiling ball kits (SCB1-52) are available for slope angles greater than 30° and up to 52°. Call technical support for more information.

LOCATION USE:

Fan is rated for dry and damp locations.

Available Finishes	
MG	Metro gray
OB	Oil-rubbed bronze

TUV/GS Efficiency Info (220V)			
Fan Speed	Max RPM	Amps	Watts
High	105	0.24	55.2
Med	71	0.19	28.7
Low	51	0.13	14.8